



MATERIAL SAFETY DATA SHEET

Product Code: F818-Line

Issue Date: 7/10/2010

Issue No.2

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name	AUSTRALIS OIL BASED ENAMEL – SEMI GLOSS
Product Code	818-100, 818-222, 818-333
Company Name	Colourtrend Paints Australia Pty Ltd (ABN) 50 057 442 323
Address	481 Victoria Street Wetherill Park N.S.W. 2164 AUSTRALIA
Phone	02 97562400
Fax	02 97562405
Emergency	0439 624 009
Product Use	Use as a decorative & protective coating on timber structures. Applied by brush, roller, conventional spray or airless spray.

2. HAZARDS IDENTIFICATION

This material is hazardous according to criteria of Safe Work Australia
Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code for transport by Road & Rail.

Risk Phrases	Flammable. Irritating to skin
Poisons Schedule	None allocated

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Characterisation	Liquid																								
Ingredients	<table><thead><tr><th><u>Name</u></th><th><u>CAS Number</u></th><th><u>Proportion</u></th></tr></thead><tbody><tr><td>Kerosene</td><td>8008-20-6</td><td><10%</td></tr><tr><td>White Spirit</td><td>8052-41-3</td><td>10-30%</td></tr><tr><td>Mineral Turps</td><td></td><td>10-30%</td></tr><tr><td>Xylene</td><td>1330-20-7</td><td><10%</td></tr><tr><td>Pigments</td><td></td><td>30-60%</td></tr><tr><td>Synthetic Polymers</td><td></td><td>30-60%</td></tr><tr><td>Other ingredients determined not to be hazardous</td><td></td><td>to 100%</td></tr></tbody></table>	<u>Name</u>	<u>CAS Number</u>	<u>Proportion</u>	Kerosene	8008-20-6	<10%	White Spirit	8052-41-3	10-30%	Mineral Turps		10-30%	Xylene	1330-20-7	<10%	Pigments		30-60%	Synthetic Polymers		30-60%	Other ingredients determined not to be hazardous		to 100%
<u>Name</u>	<u>CAS Number</u>	<u>Proportion</u>																							
Kerosene	8008-20-6	<10%																							
White Spirit	8052-41-3	10-30%																							
Mineral Turps		10-30%																							
Xylene	1330-20-7	<10%																							
Pigments		30-60%																							
Synthetic Polymers		30-60%																							
Other ingredients determined not to be hazardous		to 100%																							

4. FIRST AID MEASURES

In an emergency Contact Poisons Information Centre in Australia (13 1126) for advice

Swallowed	If swallowed drink 2 glasses of water and seek medical advice from a physician if required
Eye	Flush eyes with copious quantities of water for at least 15 minutes. Seek medical attention.
Skin	Remove all contaminated clothing/footwear and wash skin with running water. If irritation persists seek medical advice from a physician.

COLOURTREND PAINTS AUSTRALIA PTY LTD - MSDS**Product Code: F818-Line****Issue Date: 7/10/2010****Issue No.2**

Inhaled	Remove from contaminated area. Remove contaminated clothing. Apply air resuscitation if breathing is irregular or stopped. Seek medical attention.
First Aid Facilities	Eye wash and safety shower facilities should be available.
Advice to doctor	Treat symptomatically

5. FIRE FIGHTING MEASURES

Specific Hazards	Flammable liquid. Avoid all ignition sources. Do not smoke.
Extinguishing Media	On burning will emit toxic fumes. Use foam, dry chemical, carbon dioxide.
Fire fighting advice	Avoid contamination with oxidising agents. Fire fighters and others exposed to vapours or products of combustion should wear self-contained breathing apparatus and suitable protective clothing.

6. ACCIDENTAL RELEASE MEASURES

Minor Spills	Clean up all spills immediately. Place in a suitable labelled container for waste disposal.
Major Spills	Contain/prevent run off into drains and waterways. Shut off all possible sources of ignition. Wear protective clothing to prevent skin and eye contact. Avoid breathing in vapours. Contain spill with sand, earth or vermiculite. Alert Fire Brigade if necessary. Collect recoverable material and seal in properly labelled containers or drums for disposal.

7. HANDLING AND STORAGE

Handling	Wear protective clothing. Avoid physical damage to containers. Always wash hands with soap and water after handling.
Storage	Store in cool dry well ventilated place and out of direct sunlight. Keep containers sealed when not in use. Avoid contact with incompatible materials. Checked all containers are clearly labelled & free from leaks. Follow manufacturer's storing & handling recommendations.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits	No exposure limits set by NOHSC. However, Exposure Standard(s) for constituent(s): White Spirit: 8hr TWA = 790mg/m ³ Mineral Turps: 8hr TWA = 480mg/m ³ Xylene: 8hr TWA = 350mg/m ³
Engineering Control Measures	Use under well ventilated conditions. If use indoors, open all windows and doors. Seal containers closed when not in use
Personal Protection	If there is a risk of eye contact, repeated or prolonged skin contact or inhalation, wear gloves, safety glasses and a respirator. Wash hands prior to smoking, eating and drinking.

9. PHYSICAL AND CHEMICAL PROPERTIES

<u>PHYSICAL DESCRIPTION & PROPERTIES</u>	Appearance	:	Viscous liquid
	Odour	:	Solvent
	Colour	:	Coloured
	Boiling Point	:	Not applicable
	Melting Point	:	Not Available
	Specific Gravity	:	1.0 – 1.4 at 20 ⁰ C
	Flash Point	:	>23 ⁰ C
	Flammability Limits	:	Not Available
	Solubility in water	:	Insoluble in water. Soluble in organic solvents
	pH as supplied	:	Not Applicable
	Vapour pressure (20 ⁰ C)	:	Not Available
	Evaporation rate	:	Not Available
	Autoignition Temp (C)	:	Not Available
Volatile (% Wt.)	:	Not Available	
Decomposition Temp(C):	:	Not Available	

10. STABILITY AND REACTIVITY

Stability Incompatible with oxidising agents

11. TOXICOLOGICAL INFORMATION

No adverse effects expected if the product is handled in accordance with this Safety Data Sheet and the label of this product. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Eye May produce eye irritation

Skin Contact with skin may results in irritation

Inhaled The vapour or mist may irritate to mucous membranes of the respiratory tract. This may cause headache and nausea.

Swallowed Swallow may result in nausea, abdominal irritation and vomiting

12. ECOLOGICAL INFORMATION

Avoid contaminating waterways and disposing of paint or washings into drains or stormwater channels.

13. DISPOSAL CONSIDERATIONS

Recycle wherever possible. Refer to Waste Management Authority. Dispose of material through a licensed waste contractor. Unwanted paint should be allowed to dry and then disposal of via domestic waste collection. Empty paint cans should be left open in a good ventilated area to dry before disposal. Consult your State Land Waste Management Authority prior to disposal.

14. TRANSPORT INFORMATION

Road and Rail Transport	Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail. UN No: 1263 Class-primary: 3 Flammable Liquid Packing Group: 111 Proper Shipping Name: PAINT Hazchem Code: 3[Y]
Marine Transport	Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea. UN No: 1263 Class-primary: 3 Flammable Liquid Packing Group: 111 Proper Shipping Name: PAINT
Air Transport	Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air. UN No: 1263 Packing Group: 111 Proper Shipping Name: PAINT

15. REGULATORY INFORMATION

Classification	Classified as hazardous according to criteria of NOHSC. Xi: Irritant
Poisons Schedule	None allocated
A.I.C.S. Status	All components of the finished product are listed on the Australian Inventory of Chemical Substances (AICS).
Risk Phrase(s)	R10: Flammable R38: Irritating to skin
Safety Phrase(s)	S16: Keep away from ignition source – no smoking S24: Avoid contact with skin S28: If contact with skin, wash immediately with plenty of soap & water

16. OTHER INFORMATION

This material safety data sheet prepared by Colourtrend Paints Australia Pty Ltd.